



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage

Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit FA Floor Sleeve NG

Technical Data Sheet

01.12.2021

Elastic sleeve for a permanent sealing of floor drains in combination with sealing systems under tiles.

Properties:


Kaubit FA Floor Sleeve NG is watertight, permanently elastic sealing. The packing is made from NBR-Rubber with a centrally inserted fabric layer. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the packing.

Applications:

Kaubit FA Floor Sleeve NG is used to permanently waterproof ground drains. The packing is complete embedded into the sealing compound.

Technical specifications:

Measurements:	350 x 350 mm
Thickness:	0.8 mm
Temperature resistance:	-20°C to +90°C



Supplied as:

5 pieces / carton
10 pieces / carton

Preparation of the substrate:

The preparation of the surface depends on the respective waterproofing system used.

Use:

The Kaubit FA Floor Sleeve NG is put over the drain passage, laid and pressed into the fresh sealing mass. When applying the second coating with the sealing mass the entire packing is coated as well. When the waterproofing system has to be applied in one coat the packing is laid into a previously applied thin layer of the system before the system is applied over the whole area. The required hole for the ground drain has to be made beforehand as per requirement at site.

Information on further processing:

Kaubit FA Floor Sleeve NG is absolutely silicone-compatible; a soaking must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the Kaubit FA Floor Sleeve NG. Before applying further products a compatibility test has to be carried out.

Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.

Storage:

Kaubit FA Floor Sleeve NG can be used for a period of at least 24 months when stored in a cool and dry period.

Further units available on request.

Safety information:

The product is not hazardous as defined in the (German) Hazardous Substances Code.

Disposal:

May be disposed of as building site waste.