



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage
Telefon: (0 44 43) 96 69-0 • Fax: (0 44 43) 96 69-66 • Internet: <http://www.kaubit.de> • E-Mail: info@kaubit.de

Kaubit FA Sealing Tape NVV 200 / 250 / 500

Technical Data Sheet

01.12.2021

Permanently elastic and fleece-coated sealing tape based on NBR rubber with high transverse expansion, especially for sealing movement joints

Properties:

Kaubit FA Joint Tape NVV 250 is an elastic sealing tape on the basis of NBR rubber. The Tape has a good rebound resilience. NBR rubber has an excellent compatibility with all commonly used, solvent-free coatings, also fixed with solvent-free epoxy resin.

Applications:

Kaubit FA Sealing Tape NVV has been developed for waterproofing wet rooms and especially for the difficult field of movement joints.

Technical specifications:

Thickness:	0,90 mm
Standard widths:	200 mm 250 mm 500 mm
Colour	blue, green
Weight:	0,9 kg / m ²
Sd value:	5 m
Application temperature:	-20°C bis +90°C

Preparation of the substrate in wet rooms:

The surface has to be solid, stable and flat, as well as free of oil, grease, dust. The preparation of the substrate depends on the type and composition of the substrate and the intended sealing system. A suitable primer must be applied. After the primer has dried, you can glue the tape with a sealant and coat over afterwards, at least 5 cm beyond the tape.

Use:

Cut the sealing tape to the required length and insert it into the still fresh seal, which acts as a bounding agent. Make sure the strips are overlapped by at least 5 cm. Unevenness or distortions can be pressed down with a smoothing trowel. Finally, apply 2 to 3 coats over the entire area and coat the sealing tape completely with the sealant.

Consumption:

Consider an overlapping of at least 5 cm as per requirement.



Information on further processing:

The raw material provides excellent compatibility and a good bond with polymer dispersions, mineral flexible sealing slurries and reactive resins. Before further products are applied, it is advisable to carry out a compatibility test.

Cleaning tools and equipment:

Tools are to be cleaned with water immediately after use.

Storage:

When stored in a cool and dry place in original packaging: 24 months

Supplied as 200 mm version:

rolls à 30 m
1 roll / carton
45 cartons / pallet

Further roll lengths and widths available on request.

Safety information:

Not a hazardous substance according to the Ordinance on Hazardous Substances.

Disposal:

Can be disposed of as construction waste.



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage
Telefon: (0 44 43) 96 69-0 • Fax: (0 44 43) 96 69-66 • Internet: <http://www.kaubit.de> • E-Mail: info@kaubit.de