



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit FA Sealing Tape PEVV

Technical Data Sheet

01.12.2021

Sealing tape for durable sealing in combination with sealing systems under tiles.

Properties:

Kaubit FA Sealing Tape PEVV is water-tight and durable sealing. The sealing tape is made of polyethylene foil with double side fleece coating. By means of this material basis, an excellent bonding over the entire surface of the shape is achieved with almost every sealing material implemented beneath tiles.

Applications:

For use in corners and to cover joints.

Technical specifications:

| | |
|----------------------------|---------|
| Width: | 120 mm |
| Thickness: | 0.4 mm |
| Material weight: | 22 g/ m |
| Elongation: | 60 % |
| Water pressure resistance: | 3 bar |

Preparation of the substrate:

This will depend on the nature and form of the substrate and the sealing system to be used. A suitable primer should be first applied (see Table of Applications). After the primer has dried, a band of sealant compound should be applied which is approximately 5 cm wider than the sealing tape on either side.

Use:

The Sealing Tape is laid onto the fresh coating of the sealing material which serves as an adhesive base here. An overlapping of the sealing tape of at least 5 cm has to be considered. Uneven areas or folds can be pressed on by using a hand float. Finally 2-3 more coats of the areas to be sealed have to be applied by coating the sealing tape as well.

Consumption:

An overlapping of the sealing tape of at least 5 cm has to be considered when calculating the consumption.

Information on further processing:

Kaubit FA Sealing Tape PEVV is absolutely silicone-compatible; a saponification must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the sealing tape. Before applying further products a compatibility test has to be carried out.



Cleaning of tools and equipment:

Rinse tools and dirtied areas with water immediately after usage.

Storage:

Kaubiflex FA Sealing Tape PEVV can be used for a period of at least 24 months when stored in a cool and dry place.

Supplied as:

50 m rolls
25 m rolls
10 m rolls

Further sizes available on request.

Safety information:

This product is not hazardous as defined in the (German) Hazardous Substances Code.

Disposal:

May be disposed of as building site waste.