



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage  
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

# Kaubit FA Wall Sleeve PEVVN

## Technical Data Sheet

01.12.2021

**Double-sided, fleece-coated wall sleeve for a permanent sealing of pipe passages in combination with sealing systems under tiles.**

### Properties:

Kaubit FA Wall Sleeve PEVVN is watertight, permanently sealing. The sleeve is made of polyethylene foil reinforced with on both sides with non-woven and a flexible zone based on NBR rubber in the middle. This material basis causes an excellent bonding with almost any waterproofing materials used under tiles extending over the entire surface of the sleeve.

### Applications:

Kaubit FA Wall Sleeve PEVVN is suitable as permanently watertight sealing on wall areas for pipe passages of shower and bathtub water fittings under ceramic coverings. The sleeve is completely embedded into the sealing material.



### Technical specifications:

Total measurements:	120 x 120 mm 150 x 150 mm 200 x 200 mm 250 x 250 mm
Flexible zone based on NBR rubber:	size on request
Diameter hole:	hole on request

### Preparation of the substrate:

The preparation of the surface depends on the respective waterproofing system used.

### Use:

The wall sleeve is put over the pipe passage, laid and pressed into the fresh sealing mass. When applying the second coating with the sealing mass the entire packing is coated as well. When the waterproofing system has to be applied in one coat the packing is laid into a previously applied thin layer of the system before the system is applied over the whole area.

### Information on further processing:

Kaubit FA Wall Sleeve PEVVN is absolutely silicone-compatible; a soaking must not be expected. For lining the joints usual silicones may be applied. Solvent-free adhesives and coatings may be applied directly onto the wall sleeve. Before applying further products a compatibility test has to be carried out.

### Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.

### Storage:

Kaubit FA Wall Sleeve PEVVN can be used for a period of at least 24 months when stored in a cool and dry place.

### Supplied as:

20 pieces / carton  
25 pieces / carton

### Further units available on request.

### Safety information:

The product is not hazardous as defined in the (German) Hazardous Substances Code.

### Disposal:

May be disposed of as building site waste.