



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage  
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

## Kaubit Joint Paint

## Technical Data Sheet

01.12.2021

**Water- and dirt-resistant joint paint to freshen up the appearance of mortar grouting on ceramic wall and floor coverings.**

### Properties:

The matt-setting, water-based joint paint is ready to use, and is resistant to water and dirt. It is odourless and dries quickly when used. It is resistant to alkaline sub-surfaces and non-abrasive detergents such as soaps and shampoos.

### Applications:

Used to freshen up the appearance and change the tone of mortar grouting on indoor ceramic wall and floor coverings.

### Technical specifications:

Working temperature: > 5°C  
Colour: white, grey  
Viscosity: 10.000 mPa·s  
Density: 1.55 g/cm<sup>3</sup>  
pH value: 8.5

### Preparation of the substrate:

The grouting mortar must be hard, stable and free of dust, dirt, oil, grease and loose parts. Brittle, damaged grouts must be scratched out and renewed. Greasy, mouldy or dirty grouting mortar must be cleaned with a sponge and household cleaning agent. Any lime residue must be removed. Rinse the cleaned surfaces with lots of water, and leave to dry.

### Use:

Mix well before usage, and apply smoothly and evenly using only the brush provided. Apply approx. 1 to 2 mm beyond the edge of the grouting.

Wet the entire tiled area somewhat after approx. 60 minutes, wait approx. 5 minutes and then remove the excess paint, which has swelled from the wetting, from the tiles using the hard side of the moist sponge in a diagonal or circular motion, until the sharp edges of the grouting can again be seen.

Then immediately clean the entire area with an almost dry sponge (soft side), and leave to dry. The area can be cleaned again after it has been left to dry for a few hours.

### Consumption:

Usage depends on the tile format and grouting width. 250 ml is enough for approx. 10 to 15 m<sup>2</sup>.



### Drying time:

Drying time is approx. 1 hour at room temperature. In shower areas, allow at least 2 days of drying after work is completed before exposing it to water for the first time.

### Cleaning of tools and equipment:

Rinse tools and dirtied areas with water immediately after usage.

### Storage:

12 months in a cool, frost-free place in original sealed container.

### Supplied as:

Set contains  
- 250 ml bottle of Kaubit Joint Paint  
- 1 round brush  
- 1 sponge

12 sets per box  
64 boxes per pallet

### Safety information:

Not a hazardous substance according to the Ordinance on Hazardous Substances.

### Disposal:

Can be disposed of as construction waste.

**For further information see also Material Safety Data Sheet (MSDS).**