



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage

Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit PVC-Adhesive

Technical Data Sheet

01.12.2021

Floor adhesive, suitable for gluing most types of PVC, LVT and textile floor coverings.

Properties:

Easily applicable, fast setting floor adhesive with an excellent bonding to mineral surfaces. Very good tack and long assembly time. For floor heating.

Applications:

Suitable for surfaces, which are sufficiently stable as screed and heated screed, concrete, masonry, aerated concrete and plasters.

Technical specifications:

Application temperature:	> +5°C
Viscosity:	approx. 15.000 mPa·s
Density:	ca. 1,2 g/cm ³
Solid content:	ca. 76 %
pH-value:	8.0

Preparation of the subfloor:

Concrete and sand/cement screeds must be fully cured and any laitance or surface treatments must be removed.

Before installing the covering make sure that the subfloor is clean, even and dust free and has an adequate strength, bearing strength, dimensional stability and is permanent dry.

The moisture content in the concrete must not exceed 75%

When gluing rubber or chlorine free coverings, ensure the surface strength of the subfloor is minimum 1,0 M.

Highly absorbent subfloors should be primed with PVC Adhesive diluted 1 to 4 parts of water and stirred until thoroughly dispersed. This should be applied and allowed to dry thoroughly before proceeding with the installation.

Use:

Apply the adhesive using a trowel or a roller. Try to obtain a smooth, uniform appearance. This will minimise adhesive grin through and maximise surface area of contact for adhesion. Floorcoverings can be placed into the adhesive immediately although it is advisable, when installing tiles, to leave the adhesive for approximately 10 minutes before placing the flooring, reducing the potential for sliding.

On **non-absorbent surfaces** allow the adhesive to dry to a firm tack before laying the floorcovering.



Roll tiles immediately after placement into the dry adhesive film using a flooring roller.

Consumption:

The coverage is about 0,2 -0,3 kg/m².

Packaging:

5 kg bucket	10 kg bucket
100 buckets / pallet	48 buckets / pallet

Further sizes available on request.

Storage:

12 months in unopened containers stored under good conditions, between 5°C and 30°C. Protect from frost.

Cleaning of tools and equipment:

Tools as well as dirty areas have to be cleaned with water immediately after use.

Safety information:

Not a hazardous substance according to the Ordinance on Hazardous Substances.

Kaubit PVC Adhesive must be kept away from children.

Disposal:

Can be disposed of as construction waste.

For further information see also Material Safety Data Sheet (MSDS).