



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit FA Outside Corner PEVB Technical Data Sheet

01.12.2021

Self-adhesive, alkali-resistant and fleece-coated shape for durable sealing of outside corners in combination with sealing systems under tiles.

Properties:

Kaubit FA Outside Corner PEVB is water-tight, durable-elastic sealing. The self-adhesive butyl Outside Corner is made of polyethylene with fleece coating. This material base combination has an excellent bonding over the entire surface of the shape is achieved with almost every sealing material used beneath tiles.

Applications:

Kaubit FA Outside Corner PEVB is used as durable, watertight sealing in corners beneath ceramic coverings. The outside corner needs to be covered fully with the right sealant used.

Technical specifications:

Working temperatures:	+5°C
Leg length:	105 mm
Width:	120 mm
Thickness:	0,7 mm

Preparation of the substrate:

Preparation of the grounds is done according to the sealing system used.

Use:

The preparation of the substrate depends on the type and composition of the substrate and the intended sealing system. A suitable primer must be applied. After the primer has dried, the shaped piece can be glued directly to the substrate.

Information on further processing:

Remove the first half of the backside PE liner and press it firmly onto the intended surface. Then remove the second half of the liner and press the self-adhesive corner to the surface. If the PE film cannot be detached from the butyl, it must not be pulled any further. The adhering point has to be loosened carefully. The film can only be peeled off further once this has been released.

These adhesions can be caused by pressure points in the butyl which can be traced back to incorrect storage. The corner must be correctly positioned the first time it is glued on. Correction only works to a limited extent, depending on the subsurface.

For safety reasons, the self-adhesive butyl corner must be replaced with a new one



Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water

Storage:

Kaubit FA Outside Corner PEVB can be used for a period of at least 24 months when stored in a cool and dry place.

Supplied as:

10 pieces / carton
25 pieces / carton

Further units available on request.

Safety information:

The product is not hazardous as defined in the (German) Hazardous Substances Code.

Disposal:

May be disposed of as building site waste.