



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage
Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

Kaubit FA Sealing Tape NVV with Cut Protection

Technical Data Sheet
01.12.2021

Both side fleece coated NBR rubber elastic sealing tape reinforced with cut protection through Aramid fibers

Properties:

Both side with non-woven coated NBR rubber elastic sealing tape with cut protection (Aramid fibers) in the center. The tape exhibits excellent recovery characteristics and is fully silicone compatible.

Applications:

For use in corners and to cover joints for internal and external application.

Technical specifications:

Thickness:	0.60 mm
Thickness with Aramid fibers	0,95 mm
Width:	140 mm
Cut protection: Aramid fibers	2 x 20 mm
Weight:	50 g/m
Equivalent air layer thickness sd:	5 m
Water pressure resistance:	leakproof at 3 bar
Temperature resistance:	-20°C to +90°C

Preparation of the substrate:

This will depend on the nature and form of the substrate and the sealing system to be used. A suitable primer should be first applied (see Table of Applications).

Use:

Cut the sealing tape to the required length and press onto the fresh Kaubiflex FA Sealing Compound, which serves as the adhesive base. Ensure that there is a tape overlap of at least 5 cm. Use a smoothing trowel to level out any uneven areas or distortions. Apply two or three coats and ensure that the tape is fully covered with Kaubiflex FA Sealing Compound or other sealants.

Consumption:

When calculating consumption, allow for a tape overlap of at least 5 cm.

Information on further processing:

The tape ensures excellent compatibility and good adhesion with polymer dispersions, flexible mineral sealing compounds and thermosetting resins. However, it is advisable to conduct a compatibility test before applying other products.

Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.



Storage:

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

Supplied as

25 m roll
Carton á 1 roll

Further sizes available on request.

Safety information:

This product is not hazardous as defined in the (German) Hazardous Substances Code.

Disposal:

May be disposed of as building site waste.