



Systemabdichtungsbaustoffe

KAUBIT Aktiengesellschaft • Industriestraße 1 • 49413 Dinklage

Telephone: +49 4443 9669-0 • Telefax: +49 4443 9669-66 • Internet: www.kaubit.de • E-Mail: info@kaubit.de

# Kaubit FA Sealing Tape PEVB

## Technical Data Sheet

01.12.2021

### Special and self-adhesive butyl tape, reinforced with non-woven and polyethylene foil for sealing under ceramic tiles in wet rooms

#### Properties:

Fleece coated, alkali resistant, reinforced with polyethylene foil, permanently elastic innovative butyl sealing tape with a high adhesive strength and tear resistance. The fleece coating allows an excellent combination with common sealants as polymer dispersions and mineral flexible sealing slurries and reaction resins.

#### Applications:

For use in corners and to cover joints of membranes in wet rooms.

#### Technical specifications:

<b>Thickness:</b>	<b>0.65 mm</b>
<b>Width:</b>	<b>100 mm</b>
<b>Working temperature</b>	<b>+5°C</b>
<b>Thickness:</b>	<b>0.75 mm</b>
<b>Width:</b>	<b>250 mm</b>

#### Preparation of the substrate:

This will depend on the nature and form of the substrate and the sealing system to be used. A suitable primer should be first applied.

#### Use:

Cut the sealing tape to the required length. Remove the silicone strip and press firmly to the intended surface. The sealing strip must be positioned correctly at the first try. A correction is possible conditionally and depends on the substrate. For safety reasons, the sealing strip must be replaced by a new section.

#### Consumption:

When calculating consumption, allow for a tape overlap of at least 5 cm.

#### Information on further processing:

The tape ensures excellent compatibility and good adhesion with polymer dispersions, flexible mineral sealing slurries and reaction resins. However, it is advisable to conduct a compatibility test before applying other products.

#### Cleaning of tools and equipment:

Tools and soiled areas should be cleaned immediately after use with water.



#### Storage:

Can be stored in the original sealed packaging for up to 24 months in a cool, dry environment.

#### Supplied as:

##### 100 mm:

10 m roll	20 m roll
400 cartons / pallet	120 cartons / pallet

##### 250 mm:

10 m roll
105 cartons / pallet

Further widths and roll lengths available on request.

#### Safety information:

This product is not hazardous as defined in the (German) Hazardous Substances Code.

#### Disposal:

May be disposed of as construction waste.